

Technical File

Art. FM003



DESCRIPTION

FFP1 cup-shaped respirator with exhalation valve for less breathing resistance and less warmth inside the mask. Comes with adjustable metal nose strip and elastic straps for optimised fit.

CHARACTERISTICS

- CAT III, FFP1 NR D respirator
- Used for protection from dust particles up to 4x the Threshold Limit Value (TLV)
- Passed optional Dolomite test ("D") and therefore suited for all-day use (8 hours)
- Cup-shaped
- With exhalation valve for less breathing resistance and less warmth inside the the mask
- Non-reusable
- Large inner space for easy breathing
- Metal nose piece
- Elastic strap

APPLICATIONS

This respirator can be used for work found in sectors such as:

- pharmaceutical industry
- medical/hospital
- veterinary
- DIY
- cleaning
- food processing
- manufacturing

SIZES

One size

MAINTENANCE - STORAGE

Store in its original package in a dry environment at room temperature and protected from direct sunlight.

PRACTICAL INFORMATION

Packing quantities: 12pcs per inner box, 20 inner boxes per carton (total 240pcs).

Carton size: 64x30x36cm

Qty per pallet: 20 cartons (4.800pcs)



CERTIFICATIONS

CE in accordance with **EU Regulation 2016/425**
CAT III

EN149:2001+A1:2009

FFP1 NR D