

# GL008C

# TECHNICAL DATASHEET



EN

## DESCRIPTION

- Protection against the impact of objects
- Protection against splashes of molten metal
- Protection against light spray and aerosols
- Suitable for work in slightly humid conditions
- Protection against airborne solid particles
- Suited for continuous use

## CHARACTERISTICS

|                     |  |
|---------------------|--|
| Type:               | Safety spectacles  |
| Lens material:      | Polycarbonate  |
| Colour:             | Transparent  |
| Coating:            | Anti-fog   |
| Frame material:     | TPR  |
| Colour:             | Orange   |
| Weight:             | 82g  |
| Ventilation:        | Indirect   |
| Protection against: | Medium energy impact (120m/s)<br>Molten metals and hot solids<br>Extreme temperatures (-5°C - +55°C) |
| Elastics:           | Elastic band   |
| Other attributes:   | Panoramic view   |

## SIZES

|                     |          |
|---------------------|----------|
| Available in sizes: | One size |
|---------------------|----------|

## FIELDS OF USE

- |                   |                       |
|-------------------|-----------------------|
| - Construction    | - Automotive industry |
| - Manufacturing   | - DIY                 |
| - General purpose | - Metallurgy          |

## PRACTICAL INFORMATION

|                            |                             |
|----------------------------|-----------------------------|
| Packaging method:          | Commercial retail packaging |
| Quantity per polybag:      | 1                           |
| Quantity per inner box:    | 12                          |
| Quantity per outer carton: | 120                         |
| Shelf life (months):       | 60                          |



## CERTIFICATIONS



CAT II

In accordance with Regulation (EU) 2016/425  
EN 166:2001

1 BT 9 CE



EN166 3 9 BT CE



Sacobel B.V.  
Takkebijsters 15H  
4817 BL Breda  
Netherlands

T. +31 (0)76 571 1111  
info@sacobel.com  
www.sacobel.com

VAT: NL009448949B01  
COC: 20056214  
GL008C EN datasheet

Version: 3-3-2021